

Electrical Characteristics

Typical Performance at Standard Test Conditions (STC)

For irradiance of 1000W/m² with AM1.5 spectrum and cell temperature of 25°C.

Peak Power	P _{max}	11.5W
Voltage at P _{max}	V _{mp}	19.0V
Current at P _{max}	I _{mp}	0.61A
Open-circuit voltage	V _{oc}	23.4V
Short-circuit current	I _{sc}	0.70A
Warranted power	P _{war}	9.0W

Refer to the Warranty documents for more information.

Temperature Coefficients

For irradiance of 1000W/m² with AM1.5 spectrum.

T(P _{max})	-0.35% / °C
T(V _{oc})	-70mV / °C

Module Limits

Max. system voltage (Aus)	30V
Min. operating temperature	-40°C
Max. operating temperature	85°C

Warranty

This product has a 1/10 year warranty.

Warranty documents can be found on our website.

For Further Information

Please read the Installation Manual on our website www.SLIVER.com.au or email solarenergy@originenergy.com.au

Mechanical Specifications

The double glass construction and corrosion-resistant anodized aluminium frame provides excellent durability, even under extreme weather conditions.

External dimensions	461mm x 352mm
Width	40mm
Weight	3.8kg
Length of cable	1000mm

