

Together we can
make a difference.™



Origin2760 2.76kW Solar System Inverter Specifications

Your Origin2760 system will be supplied with the following inverter(s):

- Delta Solivia 3.0

Please note the inverter supplied with your solar system is AS4777 accredited.

Please see the following specification sheet for further details and inverter specifications.

SOLiVi4 3.0



3000 Watt Solar Inverter

Delta, with over 70 years of power electronics experience, presents high efficiency solar inverters designed in Germany. SOLIVIA stands for "SOLar Inverters for Versatile and Intelligent Applications". The 3rd generation of our solar inverters offers cutting-edge and outstanding SOLIVIA features with output power from 2.5 kW to 5.0 kW.



Efficiency & temperature

The brand new SOLIVIA inverters for Australian market have a maximum efficiency of 96%, do not have fans, are dust tight (IP65), and operate over a wide range of temperatures.



Versatile applications

The SOLIVIA string inverters can be used with all common photovoltaic module types, even with back-contact and thin-film modules that require positive or negative DC grounding. With the optional grounding kit from Delta, the SOLIVIA inverters are a perfect fit for these applications.

INPUT (DC)	
Max. recommended PV power	3650 W
Nominal power	3300 W
Voltage range	125 ... 540 V
MPP range	150 ... 450 V
Full power MPP range	150 ... 450 V
Nominal current	11.8 A
Max. current	22.0 A
Stand-by power	< 0.2 W

GENERAL SPECIFICATION	
Model name	SOLIVIA 3.0 AP G3
Max. efficiency	96.0 %
Efficiency EU	94.8 %
Operating temperature	-25 ... +70 °C
Storage temperature	-25 ... +80 °C
Humidity	0 ... 98 %

MECHANICAL DESIGN	
Size (L x W x D)	410 x 410 x 180 mm
Weight	21.5 kg
Cooling	Free convection
AC connector	Wieland RST25i3S
DC connector	4 pairs of Multicontact MC4
Communication	2 Harting RJ45 / RS485
Display	3 LEDs, LCD

OUTPUT (AC)	
Max. power	3170 W
Nominal power	3000 W
Voltage range	210 ... 264 V
Nominal current	13.0 A
Max. current	14.3 A
Nominal frequency	50 Hz
Frequency range	48.0 ... 52.0 Hz
Power factor (cos φ)	> 0.99 @ nominal power
Total harmonic distortion (THD)	< 5 % @ nominal power

STANDARDS	
Protection degree	IP65
Safety class	1
Configurable trip parameters	Yes
Insulation monitoring	Yes
Anti-islanding protection	AS 4777.2; AS 4777.3; IEC 60255.5

DIRECTIVES	
EMC	AS 4777.1; AS 4777.2; AS 4777.3; EN 61000-6-2; IEC / EN 61000-6-3
Safety	AS/NZS 60950; AS/NZS 3100; AS 4777.2; AS 4777.3

Delta Energy Systems (Australia) Pty. Ltd.
 Suite 13, Level 4, 150 Albert Road,
 South Melbourne, VIC 3205, Australia
 General inquiry: +61 3 8414 8293
 Technical support: +61 3 8414 8295
 Email: sales.australia@solar-inverter.com
 www.solar-inverter.com

