

Together we can  
make a difference.™



## **Origin1750 1.75kW Solar System Inverter Specifications**

Your Origin1750 system will be supplied with the following inverter:

- 1 x Delta Solivia 2.5

Please note the inverter supplied with your solar system is AS4777 accredited.

Please see the following specification sheet for further details and inverter specifications.



# SOLIVIA 2.5 TR

High efficiency solar inverters for the Australian market -  
Perfect choice for a single or multi-family house

## Versatile applications

- Usable with all commercially available solar modules (mono, poly, amorphous)
- Wide input voltage range
- Suitable for indoor and outdoor applications (IP65)

## Maximum profitability

- Peak efficiency of 96 %
- Full output power up to 55 °C
- 10 years standard guarantee

# 2500 Watt solar inverters

## Technical data SOLIVIA 2.5 TR

INPUT (DC)	SOLIVIA 2.5 AP G3 TR
Max. recommended PV power	3100 W <sub>p</sub>
Nominal power	2750 W
Voltage range	125 ... 540 V
Full power MPP range	150 ... 450 V
Nominal current	9.8 A
Max. current	18 A

OUTPUT (AC)	
Nominal power	2500 W (power limit option: 2350 W)
Voltage range	210 ... 264 V
Nominal current	10.9 A
Nominal frequency	50 Hz
Frequency range	48 ... 52 Hz
Power factor	> 0.99 @ nominal power
Total harmonic distortion (THD)	< 3 % @ nominal power

### GENERAL SPECIFICATION

Model name	SOLIVIA 2.5 AP G3 TR
Part number Delta	EOE45010272
Max. efficiency	96 %
Efficiency EU	94.8 %
Operating temperature	-25 ... +70 °C
Full power without derating	-25 ... +55 °C
Storage temperature	-25 ... +80 °C
Humidity	0 ... 98 %
Max. operating altitude	2000 m (above sea level)

### MECHANICAL DESIGN

Size (L x W x D)	410 x 410 x 180 mm
Weight	21.5 kg
Cooling	Convection
AC connector	Wieland RST25i3S
DC connector	4 pairs of Multi-Contact MC4
Communication interfaces	2 x RJ45 / RS485
Display	3 LEDs, 2-line LCD

STANDARDS / DIRECTIVES	SOLIVIA 2.5 AP G3 TR
Protection degree	IP65
Safety class	I
Configurable trip parameters	Yes
Insulation monitoring	Yes
Overload behavior	Current limitation; power limitation
Anti-islanding protection / Grid regulation	AS 4777.2; AS 4777.3; IEC 60255.5
EMC	AS 4777.1; AS 4777.2; AS 4777.3; EN 61000-6-2; IEC / EN 61000-6-3
Safety	AS/NZS 60950; AS/NZS 3100; AS 4777.2; AS 4777.3

Email: [service.australia@solar-inverter.com](mailto:service.australia@solar-inverter.com)

Tel: +61 3 9543 3720

